



# AIRLUBE

## DESCRIPTION

**AIRLUBE** is a high quality rock-drill lubricant specially formulated for pneumatic tools of the oil-lubricant type. It contains extreme pressure, anti-rust, anti-corrosion and adhesive additives.

## PROPERTIES

- Strong adhesion to rapidly moving parts of most air tools
- Protection of metal surfaces for longer tool life
- Low oil consumption
- Emulsification of moisture that may enter the drill due to presence of emulsifying agent

## GRADES

- ISO VG 100, 150, 220 and 320

## APPLICATIONS

- Air-operated tools such as jack-hammers, stoppers, drifters, wagon drill, chippers, tampers, pavement breakers and stern tubes

## QUALITY LEVELS

- It has the performance profile of:
  - AIST 224
  - Davis Brown S1.53.101 (E)
  - AGMA 9005-E02

## AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

## TYPICAL CHARACTERISTICS\*

	<b>100</b>	<b>150</b>	<b>220</b>	<b>320</b>
Color, ASTM	L2.0	L3.5	L3.5	L4.0
Density at 15°C, kg/L	0.8698	0.8900	0.8955	0.8996
Kinematic Viscosity at 40°C, cSt	94.55	153.2	218.1	316.9
Kinematic Viscosity at 100°C, cSt	11.52	15.14	19.06	24.31
Viscosity Index	99	99	98	98
Flashpoint, COC, °C	240	240	246	246

\* Only typical results and may vary per production blend