# **PETROMAR HF 3030**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE

**COMPANY** 

Product Name PETROMAR HF 3030

Product Type Petroleum Hydrocarbons with Additives

Recommended Use Marine Trunk Piston Engine Oil

Company Information PETRON CORPORATION

San Miguel Head Office Complex

40 San Miguel Avenue, Mandaluyong City

**PHILIPPINES** 

General Contact Numbers (632) 8-884-9200

Website www.petron.com

SECTION 2: HAZARDS IDENTIFICATION

**GHS CLASSIFICATION** Classified as non-hazardous substance.

GHS LABELING No Hazard Symbol Required

Other Hazard Information:

Physical / Chemical Hazards No significant hazards.

Health Hazards Not expected to be a health hazard when used under normal

conditions.

Environmental Hazards Not classified as dangerous to the environment

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition	CAS Number	% Weight
Distillates (Petroleum) solvent refined heavy paraffinic	64741-88-4	80.0 – 90.0
Distillates (petroleum) hydrotreated heavy paraffinic	64742-54-7	5.0 – 10.0
Zinc Alkyl dithiophosphate	68649-42-3	< 0.30

SECTION 4: FIRST AID MEASURES

**Eye Contact** Immediately flush eyes with large amount of water for at least 15 minutes or

until irritation subsides. If irritation persists, get prompt medical attention.



**Skin Contact** Immediately flush with large amount of water; use soap if available. Remove

contaminated clothing, including shoes, and launder before reuse.

Inhalation This product is not expected to present an inhalation problem at ambient

temperature. However, if overexposed to oil mist, using proper respiratory protection, immediately remove the affected person immediately to fresh air. Administer artificial respiration if breathing is stopped. Keep at rest. Call for

prompt medical attention.

**Ingestion** If swallowed, DO NOT induce vomiting. If individual is conscious, give milk

or water to dilute stomach contents. Keep warm and quiet. Get immediate medical attention. DO NOT attempt to give anything by mouth to an

unconscious person.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point, COC, °C 250

**Extinguishing Media** In case of fire use foam, carbon dioxide or dry chemical extinguishers.

Special Fire-fighting Procedures Water jets should not be used directly on igniting products. Avoid spraying

water directly into storage containers due to danger of over-boil. However, water may be used to cool exposed containers, structures and equipment adjacent to fire. Respiratory and eye protection required for fire-fighting

personnel.

**Decomposition Products Under Fire Conditions** 

Fumes, smoke, oxides of sulfur, nitrogen, carbon and other toxic gases

may be formed.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill Taking normal safety precaution, eliminate sources of ignition. Prevent

additional discharge of material, if possible to do so without hazard. For small spills, implement cleanup procedures. For large spills, implement clean-up procedures and, if in public area, keep public away and advise authorities. Prevent liquid from entering sewers, water courses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with a suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local

disposal regulations.

Water Spill Use booms to confine spills immediately. Remove from water surface by

skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material

and ensure conformity to local disposal regulations.

SECTION 7: HANDLING AND STORAGE

Handling Procedures Keep away from potential sources of ignition. Open container in a well-

ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Wash thoroughly after handling. "Empty" containers with retained product residue (liquid or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause death or injury. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed off.

PETRON

## **Storage Procedures**

Do not store near potential sources of ignition. Store in a well-ventilated area. Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 60°C for extended periods of time or if heat sources in excess of 70°C are used.

## **SECTION 8:**

#### **EXPOSURE CONTROLS AND PERSONAL PROTECTION**

# **Exposure Controls**

Components	CAS-No.	Source	Value	
Distillates (Petroleum) solvent-refined heavy paraffinic	64741-88-4	ACGIH	5mg/m <sup>3</sup> 10 mg/m <sup>3</sup> (STEL)	
		OSHA	5mg/m <sup>3</sup>	
Distillates (petroleum) hydrotreated heavy	64742-54-7	ACGIH	5 mg/m3, TLV	
Zinc Alkyl Dithiophosphate	68649-42-3	ACGIH OSHA	5 mg/m³ (TLV) 10 mg/m³ (STEL) 5 mg/m³ (PEL)	
Kerosene	8008-20-6	NIOSH	100mg/m <sup>3</sup> (REL)	

#### **Personal Protection**

Ventilation Procedures The use of local exhaust ventilation is recommended to control mists or

vapors. Additional ventilation or exhaust may be required to maintain air

concentrations below exposure limits.

Respiratory Protection Use NIOSH/OSHA approved full-face respirator with a combination organic

vapor and high efficiency filter cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

Hand Protection Use chemical resistant gloves.

Eye Protection Where contact may occur, wear safety glasses with side shields.

Clothing Recommendation Wear either a chemical protective suit or apron when potential for contact

with material exists. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel

that could entrap the material and cause a skin reaction.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance Dark Liquid

Odor Characteristic of petroleum products

Kinematic Viscosity at 40°C, cSt 96.86
Kinematic Viscosity at 100°C, cSt 11.50
Specific Gravity at 60°F 0.9019
Flash Point, °C 256
pH No data
Boiling Point, °C No data
Melting Point, °C No data



Vapor Pressure, kPaNo dataVapor DensityNo dataSolubility in WaterInsolubleEvaporation RateNo data

Flammability Non flammable

Partition Coefficient No data
Auto-ignition Temp, °C No data
Decomposition Temp, °C No data
Explosion limits No data

SECTION 10: STABILITY AND REACTIVITY

**Stability** This product is stable and hazardous polymerization will not occur.

Incompatibility Strong oxidizing agents

Polymerization Not Applicable

SECTION 11: TOXICOLOGICAL INFORMATION

**Acute Toxicity** 

Distillates (Petroleum) solvent-

refined heavy paraffinic

Oral, LD50 >5000 mg/kg Dermal, LD50 >2000 mg/kg

Inhalation, LC50 2.18 mg/L

Distillates (petroleum),

Hydrotreated heavy paraffinic

Oral, LD50 >15000 mg/kg Dermal, LD50 >5000 mg/kg

Inhalation, LC50 >2.18 mg/L

Skin Corrosion/Irritation Low order of toxicity. Frequent or prolonged contact may cause mild skin

discomfort.

Serious Eye Damage/Irritation Will cause eye discomfort; may injure eye tissue if not removed promptly

Respiratory/Skin Sensitization There was no evidence of skin sensitization when the product was applied to

human skin.

Germ Cell Mutagenicity No available information

Aspiration Hazard Minimal toxicity

Carcinogenicity

No available information

Reproductive Toxicity

No available information

Specific Target Organ Toxicity If overheated especially in the presence of water, hydrogen sulfide may be

released. This can cause respiratory collapse, coma, even death without necessarily any odor being sensed. Avoid breathing vapor or mists. Repeated and prolonged over-exposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of

infection.



Eco-toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Environmental Mobility Oil component of this product floats and can migrate from water to

land.

Environmental Degradability Data have not been determined specifically for this product, but it is

not expected that it will be "readily" biodegradable.

Ecotoxicity & Bioaccumulation Data have not been determined specifically for this product, but it is

not expected to be harmful to aquatic organisms.

DISPOSAL CONSIDERATIONS

Waste Disposal It is the responsibility of the waste generator to determine the

toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in

compliance wth applicable regulations.

Local Legislation Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

SECTION 14: TRANSPORT INFORMATION

**Land** This product is not regulated for road/rail transport.

Sea IMDG (Packaged Goods and BLCs). This product is not regulated for sea

transport.

Air (ICAO/IATA). This product is not regulated for air transport.

SECTION 15: REGULATORY INFORMATION

Material is non-hazardous chemical under Occupational Safety and health (Classification, Labeling, and safety Data Sheet of Hazardous Chemicals) Regulations 2013.

The Chemical Substances present in this product are listed under Philippine Inventory of Chemicals and Chemical Substance (PICCS).

1

SECTION 16: OTHER INFORMATION

**Approvals** Research and Development Department

**Petron Corporation** 

This safety data sheet contains the following revisions

is safety data sheet contains the following revisions

This is a computer-generated form and does not require a signature.



The information and recommendations contained herein are based on the data sheet and sources believed to be accurate and correct and Petron makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations contained in the SDS. It is your responsibility to contact Petron to ensure that this document is the most current available from Petron. The information and recommendations are offered for the user's consideration and examination. It is the user's full responsibility to satisfy itself that the product is suitable for the intended use and to ensure the safe handling and use of the product. If the user repackages this product, it is the user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Petron accepts no responsibility and hereby disclaim all liability for any harmful effects which may be caused by purchase, resale, use, exposure or disposal of the product. Users must comply with all local laws and regulations. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "Petron" is used for convenience, and may include any one or more of Petron Corporation, Petron Oil & Gas International Sdn band or any affiliates in which they directly or indirectly hold any interest. In no event, shall Petron or its suppliers be liable for any direct or indirect loss of profits or for any other special, indirect or consequential damages, nor shall the liability of Petron on any claim for damages arising out of or connected with the sale, delivery or use of the product purchased exceed the purchase price of the product.

