

PETRON REV-X HD SAE 40 & SAE 50

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Product Name	PETRON REV-X HD SAE 40 & SAE 50
Manufacturer	PETRON CORPORATION JESUS ST., PANDACAN, MANILA PHILIPPINES
Product Type	Petroleum Hydrocarbons with Additives
Recommended Use	Diesel Engine Oil
Telephone No.	(02) 8-884-9200
Website	www.petron.com

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION	Not Classified as Hazardous Substance
GHS LABELING	
Pictogram	No symbol
Signal Word	No signal word
Hazard Statement	No hazard statement
Other Hazard Information:	
Health Hazards	Not expected to be a health hazard when used under normal conditions.
Physical / Chemical Hazards	No significant hazards.
Environmental Hazards	Not classified as dangerous to the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition	CAS Number	% Weight
Distillates (Petroleum) hydrotreated heavy paraffinic	64742-54-7	74 - 75
Highly refined mineral oil	64742-62-7	24 - 25
Zinc Alkyl Dithiophosphate	134759-18-5	< 1

SECTION 4: FIRST AID MEASURES

Eye Contact	Immediately flush eyes with large amount of water for at least 15 minutes or until irritation subsides. If irritation persists, get prompt medical attention.
Skin Contact	Immediately flush with large amount of water; use soap if available. Remove contaminated clothing and shoes, and launder before reuse.
Ingestion	If swallowed, DO NOT induce vomiting. If individual is conscious, give milk or water to dilute stomach contents. Keep warm and quiet. Get immediate medical attention. DO NOT attempt to give anything by mouth to an unconscious person.



Inhalation This product is not expected to present an inhalation problem at ambient temperature. However, if overexposed to oil mist, using proper respiratory protection, immediately remove the affected person immediately to fresh air. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point, COC, °C 242 / 280

Extinguishing Media In case of fire use foam, carbon dioxide or dry chemical extinguishers.

Special Fire-fighting Procedures Water jets should not be used directly on igniting products. Avoid spraying water directly into storage containers due to danger of over-boil. However, water may be used to cool exposed containers, structures and equipment adjacent to fire. Respiratory and eye protection required for fire-fighting personnel.

Decomposition Products Under Fire Conditions Fumes, smoke, oxides of sulfur, nitrogen, carbon and other toxic gases may be formed.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill Taking normal safety precaution, eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills, implement cleanup procedures. For large spills, implement clean-up procedures and, if in public area, keep public away and advise authorities. Prevent liquid from entering sewers, water courses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with a suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Water Spill Use booms to confine spills immediately. Remove from water surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

SECTION 7: HANDLING AND STORAGE

Handling Procedures Keep away from potential sources of ignition. Open container in a well-ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Wash thoroughly after handling. "Empty" containers with retained product residue (liquid or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause death or injury. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed off.

Storage Procedures Do not store near potential sources of ignition. Store in a well-ventilated area. Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 60°C for extended periods of time or if heat sources in excess of 70°C are used.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Controls



Components	CAS-No.	Source	Value
Distillates (Petroleum) hydrotreated heavy paraffinic	64742-54-7	ACGIH TLV	Not available
Highly refined mineral oil	64742-62-7	ACGIH SG OEL SG OEL	5mg/m ³ (TWA) 5 mg/m ³ (TWA) 10 mg/m ³ (STEL)
Zinc Alkyl Dithiophosphate	134759-18-5	ACGIH ACGIH	5 mg/m ³ (TLV) 10 mg/m ³ (STEL)

Personal Protection

Ventilation Procedures	The use of local exhaust ventilation is recommended to control mists or vapors. Additional ventilation or exhaust may be required to maintain air concentrations below exposure limits.
Hand Protection	Use chemical resistant gloves.
Eye Protection	Where contact may occur, wear safety glasses with side shields.
Respiratory Protection	Use NIOSH/OSHA approved full-face respirator with a combination organic vapor and high efficiency filter cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, poorly ventilated areas and for large spill clean-up sites.
Clothing Recommendation	Wear either a chemical protective suit or apron when potential for contact with material exists. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction.

SECTION 9:

PHYSICAL AND CHEMICAL PROPERTIES

	Rev-X HD 40	Rev-X HD 50
Appearance	Clear	Clear
Odor	Characteristic of petroleum products	Characteristic of petroleum products
Kinematic Viscosity at 40°C, cSt	132.8	203.5
Kinematic Viscosity at 100°C, cSt	14.20	18.10
Density at 15°C, kg/L	0.8806	0.8974
Flash Point, °C	242	280
pH	No data	No data
Boiling Point, °C	No data	No data
Melting Point, °C	No data	No data
Vapor Pressure, kPa	No data	No data
Vapor Density	No data	No data
Solubility in Water	Insoluble	Insoluble
Evaporation Rate	No data	No data
Flammability	Not flammable	Not flammable
Partition Coefficient	No data	No data
Auto-ignition Temperature, °C	No data	No data
Decomposition Temperature, °C	No data	No data



Environmental Degradability Data have not been determined specifically for this product, but it is not expected that it will be "readily" biodegradable.

Ecotoxicity & Bioaccumulation Data have not been determined specifically for this product, but it is not expected to be harmful to aquatic organisms.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Material, if discarded, is expected to be hazardous waste due to toxicity. Waste management should be in compliance with local and national regulations.

SECTION 14: TRANSPORT INFORMATION

Air (ICAO/IATA). This product is not regulated for air transport.

Land This product is not regulated for road/rail transport.

Sea IMDG (Packaged Goods and BLCs). This product is not regulated for sea transport.

SECTION 15: REGULATORY INFORMATION

Material is non-hazardous under Occupational Safety and Health (Classification, Labeling, and Safety Data Sheet of Hazardous Chemical) Regulations 2013.

The chemical substances present in this product are listed under Philippine Inventory of Chemicals and Chemical Substances (PICCS).

SECTION 16: OTHER INFORMATION

Approvals Research and Development Department
Petron Corporation

This safety data sheet contains the following revisions 4

This is a computer-generated form and does not require a signature.

The information and recommendations contained herein are based on the data sheet and sources believed to be accurate and correct and Petron makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations contained in the SDS. It is your responsibility to contact Petron to ensure that this document is the most current available from Petron. The information and recommendations are offered for the user's consideration and examination. It is the user's full responsibility to satisfy itself that the product is suitable for the intended use and to ensure the safe handling and use of the product. If the user repackages this product, it is the user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Petron accepts no responsibility and hereby disclaim all liability for any harmful effects which may be caused by purchase, resale, use, exposure or disposal of the product. Users must comply with all local laws and regulations. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "Petron" is used for convenience, and may include any one or more of Petron Corporation, Petron Oil & Gas International Sdn Bhd or any affiliates in which they directly or indirectly hold any interest. In no event, shall Petron or its suppliers be liable for any direct or indirect loss of profits or for any other special, indirect or consequential damages, nor shall the liability of Petron on any claim for damages arising out of or connected with the sale, delivery or use of the product purchased exceed the purchase price of the product.

