

PETRON GX 85W-140**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY**

| | |
|-------------------------|---|
| Product Name | PETRON GX 85W-140 |
| Product Type | Petroleum Hydrocarbons with Additives |
| Recommended Use | Automotive Gear Oil |
| Company Information | PETRON CORPORATION San Miguel Head Office Complex 40 San Miguel Avenue, Mandaluyong City PHILIPPINES |
| General Contact Numbers | (02) 8-884-9200 |
| Website | www.petron.com |

SECTION 2: HAZARDS IDENTIFICATION

| | |
|-----------------------------|---|
| GHS CLASSIFICATION | Not Classified as Hazardous Substance |
| GHS LABELING | |
| Pictogram | No symbol |
| Signal Word | No signal word |
| Hazard Statement | No hazard statement |
| Other Hazard Information: | |
| Health Hazards | Not expected to be a health hazard when used under normal conditions. |
| Physical / Chemical Hazards | No significant hazards. |
| Environmental Hazards | Not classified as dangerous to the environment. |

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Composition | CAS Number | % Weight |
|----------------------------|-------------|-------------|
| Highly refined mineral oil | 64742-62-7 | 95.0 - 99.0 |
| Alkyl polysulfides | Proprietary | 1.0 – 2.0 |

SECTION 4: FIRST AID MEASURES

| | |
|---------------------|---|
| Eye Contact | Immediately flush eyes with large amount of water for at least 15 minutes or until irritation subsides. If irritation persists, get prompt medical attention. |
| Skin Contact | Immediately flush with large amount of water; use soap if available. Remove contaminated clothing, including shoes, and launder before reuse. |
| Ingestion | If swallowed, DO NOT induce vomiting. If individual is conscious, give milk or water to dilute stomach contents. Keep warm and quiet. Get immediate medical attention. DO NOT attempt to give anything by mouth to an unconscious person. |



Inhalation This product is not expected to present an inhalation problem at ambient temperature. However, if overexposed to oil mist, using proper respiratory protection, immediately remove the affected person immediately to fresh air. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point, COC, °C 210

Extinguishing Media In case of fire use foam, carbon dioxide or dry chemical extinguishers.

Special Fire-fighting Procedures Water jets should not be used directly on igniting products. Avoid spraying water directly into storage containers due to danger of boil-over. However, water may be used to cool exposed containers, structures and equipment adjacent to fire. Respiratory and eye protection required for fire-fighting personnel.

Decomposition Products Under Fire Conditions Fumes, smoke, oxides of sulfur, nitrogen, carbon and other toxic gases may be formed.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill Taking normal safety precaution, eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills, implement cleanup procedures. For large spills, implement clean-up procedures and, if in public area, keep public away and advise authorities. Prevent liquid from entering sewers, water courses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with a suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Water Spill Use booms to confine spills immediately. Remove from water surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

SECTION 7: HANDLING AND STORAGE

Handling Procedures Keep away from potential sources of ignition. Open container in a well-ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Wash thoroughly after handling. "Empty" containers with retained product residue (liquid or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause death or injury. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed off.

Storage Procedures Do not store near potential sources of ignition. Store in a well-ventilated area. Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 60°C for extended periods of time or if heat sources in excess of 70°C are used.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION



Exposure Controls

| | | | |
|--------------------|------------|------------------------------------|--|
| Highly refined oil | 64742-62-7 | ACGIH TWA (Mist) STEL (Mist) | 5 mg/m ³ 5 mg/m ³ 10 mg/m ³ |
|--------------------|------------|------------------------------------|--|

Personal Protection

| | |
|-------------------------|---|
| Ventilation Procedures | The use of local exhaust ventilation is recommended to control mists or vapors. Additional ventilation or exhaust may be required to maintain air concentrations below exposure limits. |
| Respiratory Protection | Use NIOSH/OSHA approved full-face respirator with a combination organic vapor and high efficiency filter cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites. |
| Hand Protection | Use chemical resistant gloves. |
| Eye Protection | Where contact may occur, wear safety glasses with side shields. |
| Clothing Recommendation | Wear either a chemical protective suit or apron when potential for contact with material exists. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction. |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------------|--------------------------------------|
| Appearance | Clear |
| Odor | Characteristic of petroleum products |
| Kinematic Viscosity at 40°C, cSt | 403.5 |
| Kinematic Viscosity at 100°C, cSt | 28.28 |
| Density at 15 °C, cSt | 0.9060 |
| Flash Point, °C | 222 |
| pH | No data |
| Boiling Point, °C | No data |
| Melting Point, °C | No data |
| Vapor Pressure, kPa | No data |
| Vapor Density | No data |
| Solubility in Water | Insoluble |
| Evaporation Rate | No data |
| Flammability | Not flammable |
| Partition Coefficient | No data |
| Auto-ignition Temperature, °C | No data |
| Decomposition Temperature, °C | No data |
| Explosion limits | No data |

Other Information:

DMSO extract by IP346 : Less than 3.0 wt% (mineral oil component only)

SECTION 10: STABILITY AND REACTIVITY

Stability This product is stable and hazardous polymerization will not occur.



Incompatibility Strong oxidizing agents

Polymerization Not Applicable

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity

Highly refined mineral oil
Oral, LD50 >5000 mg/kg (Rat)
Dermal, LD50 >2000 mg/kg (Rabbit)
Inhalation, LC50 2.18 mg/L (Rat)

Alkyl polysulfides
Oral, LD50 2551 mg/kg (Rat)
Dermal, LD50 >2000 mg/kg (Rabbit)
Inhalation, LC50 None

Skin Corrosion/Irritation Low order of toxicity. Frequent or prolonged contact may cause mild skin discomfort.

Serious Eye Damage/Irritation May cause eye discomfort;

Respiratory/Skin Sensitization Non-sensitizing

Germ Cell Mutagenicity No available data

Aspiration Hazard Minimal toxicity

Reproductive Toxicity Not classified based on available data

Carcinogenicity EU classification of carcinogenicity of petroleum distillates used does not apply since product does not contain DMSO extract beyond 3% according to INCHEM

Specific Target Organ Toxicity Avoid breathing vapor or mists. Repeated and prolonged over-exposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of infection.

SECTION 12: ECOLOGICAL INFORMATION

Acute Toxicity

Distillates (petroleum), hydrotreated heavy paraffinic
Fish (LC₅₀ / 96-hours) >5000mg/L (Oncorhynchus)
Crustaceans (EC₅₀ / 48-hours) >1,000 mg/L (Daphnia magna)
Algae (EC₅₀ /72-hours) >1000 mg/L (Scenedesmus)

Environmental Mobility Oil component of this product floats and can migrate from water to land.

Environmental Degradability Data have not been determined specifically for this product, but it is not expected that it will be "readily" biodegradable.

Ecotoxicity & Bioaccumulation Data have not been determined specifically for this product, but it is expected to be harmful to aquatic organisms.

SECTION 13: DISPOSAL CONSIDERATIONS



Waste Disposal

Material, if discarded, is expected to be hazardous waste due to toxicity. Waste management should be in compliance with local and national regulations.

SECTION 14: TRANSPORT INFORMATION

Air (ICAO/IATA). This product is not regulated for air transport.

Land This product is not regulated for road/rail transport.

Sea IMDG (Packaged Goods and BLCs). This product is not regulated for sea transport.

SECTION 15: REGULATORY INFORMATION

Material is non-hazardous chemical under Occupational Safety and Health (Classification, Labeling, and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

The chemical substances present in this product are listed under Philippine Inventory of Chemicals and Chemical Substances (PICCS).

SECTION 16: OTHER INFORMATION

Approvals Research and Development Department
Petron Corporation

This safety data sheet contains the following revisions: **2**

This is a computer-generated form and does not require a signature.

The information and recommendations contained herein are based on the data sheet and sources believed to be accurate and correct and Petron makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations contained in the SDS. It is your responsibility to contact Petron to ensure that this document is the most current available from Petron. The information and recommendations are offered for the user's consideration and examination. It is the user's full responsibility to satisfy itself that the product is suitable for the intended use and to ensure the safe handling and use of the product. If the user repackages this product, it is the user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Petron accepts no responsibility and hereby disclaim all liability for any harmful effects which may be caused by purchase, resale, use, exposure or disposal of the product. Users must comply with all local laws and regulations. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "Petron" is used for convenience, and may include any one or more of Petron Corporation, Petron Oil & Gas International Sdn Bhd or any affiliates in which they directly or indirectly hold any interest. In no event, shall Petron or its suppliers be liable for any direct or indirect loss of profits or for any other special, indirect or consequential damages, nor shall the liability of Petron on any claim for damages arising out of or connected with the sale, delivery or use of the product purchased exceed the purchase price of the product.

